



TOOL KITS INCLUDE:

- Reaction arm and retaining rings
- Swivelling tool handle & hanger
- Two 18V / 8.0 Ah batteries with fast charger
- User manual
- Calibration certificate
- Weatherproof storage case
- QR code for safety instructions

Highlighted feature: **BUILT-IN DOUBLE SAFETY BUTTON**

The all-new B-RAD X cordless torque wrenches offer an impressive maximum torque of 15.000 Nm. Several safety enhancing features are available such as a standard handguard for added operator protection, a two-hand start and a latch lock to protect the battery from falling from heights.



More info on page 62




B-RAD X
video



Feature comparison
Page 40



Accessories
Page 42



Safety solutions
Page 62

B-RAD X



FEATURES:

- Brushless DC motor for added durability and accuracy
- Redesigned anti-fatigue trigger switch
- Standard handguard for added operator protection
- Two-hand start
- Latch lock to protect battery from falling from high heights
- 4-button interface with high contrast LED display
- Advanced cooling system
- Lithium-ion 18V battery technology
- Designed for LiHD batteries only

WHERE USED

- Tower cranes
- Wind industry
- Civil engineering



Torque range: 400 – 15.000 Nm


The most powerful cordless torque tool on the market!

RAD Torque Systems raises the bar once again with the new **B-RAD X** Series of cordless torque wrenches. The latest generation of RAD cordless torque wrenches has an impressive maximum torque of 15.000 Nm.

Building off RAD Torque's patented and world-renowned gearbox technology, the **B-RAD X** captures attention with its sleek new white design and rubber grip, a new high-performance motor, and its various features.

Fastening bolts in remote locations will now be easier for big industry as the cordless **B-RAD X** gives companies better mobility to torque and tension large bolts with less equipment to haul, without compromising power or accuracy.

Accessories on page 42



Toolkit	Tool	Drive size	Torque (Nm)		Speed	Weight	Dimensions (mm)			
Number	Model	Inches	Min	Max	RPM	Kg	L	D	W	H
30984	B-RAD X 4000	1"	400	4.000	3,8	7,8	305	81	88	345
30657	B-RAD X 7000	1½"	700	7.000	2,4	10,5	318	95	95	362
30659	B-RAD X 10K	1½"	1.000	10.000	1,7	13,8	349	108	108	369
30661	B-RAD X 15K	1½"	1.500	15.000	1,2	19,3	387	127	127	375

Repeatability of 3%